Thin Client

Ino SoC Series

4 YEARS WARRANTY

PoE

Ino SoC Series I9010, the best Citrix user experience at the lowest price

The new Ino SoC Series, optimized for Citrix HDX 3D Pro, is the ideal Zero Client to access Citrix virtual desktop infrastructures with the highest multimedia performance

- Built-in support to **Citrix XenApp & XenDesktop** infrastructures
- **Integrated GPU for 3D support and optimized DSP** for high-end multimedia performance
- Ino SoC Series I9010 can use the Citrix **HDX H.264 Enhanced SuperCodec or JPEG graphic hardware acceleration,** to provide a superior user experience and bandwidth optimization
- It provides full **HDX 3D and HDX 3D Pro support,** displaying **full HD 3D graphics rendering contents and CAD applications**, while ensuring workstations-like performance
- Is the only ARM–based System-on-Chip Thin Client with **native dual DVI support** on the market
- Is a green solution with **very low power consumption, only 8W**
- **New Power Over Ethernet factory option**
- Its **high reliability and easy remote management** through Praim ThinMan console, ensure lower Total Costs of Ownership than a traditional PC
- **Very small dimensions**, with **LCD VESA mounting kit** could be installed on the back of the monitor

CERTIFIED FOR

citrix READY HDX Premium Verified

HDX

OPERATING SYSTEM

Praim ThinOX Linux Embedded

	I9010
Processor/ Chipset	Texas Instruments DM8148 1GHZ ARM
Power supply	External 100/240VAC 50/60Hz, 12VDC / 2A max (NOT PROVIDED WITH POE FACTORY OPTION)
Power consumption: On / Stand-by	8.7W / 0.3W standard
Device dimension / weight	29 (W) x 145 (H) x 133 (D) mm, 0.600 Kg
Packaging dimension / weight	83 (W) x 232 (H) x 205 (D) mm, 1.500 Kg
Device certifications / Power supply certifications	CE, FCC Class B, Energy Star 5.0, EuP/ErP 2013 / CE, FCC Class B, GS TUV,UL
Temperature range / humidity	0° ÷ 35° / 20% ÷ 80%
Security lock	Kensington
Display resolution	1920 x 1200 Dual Monitor
Display ratio	DDC 4:3, 16:10 WIDE
Color	32 bit
Built-in speaker	Built-in 1W speaker
Operating System	ThinOX V9 for SoC
RAM memory / Flash memory	1GB / 4GB
I/O Physical	
USB ports	2 USB 2.0 front + 2 USB 2.0 rear
Video ports	1 DVI-I port + 1 DVI-D port
Audio - Mic In	1 x 1/8 inch jack
Audio - Line Out	1 x 1/8 inch jack
Networking	
RJ45 10/100/1000 Base-T Ethernet	✓
Mounting	
Vertical Stand	✓
Rear monitor mounting with Vesa kit	✓
Packaging included	
Power cord	✓
DVI-I to VGA adapter	✓
USB optical mouse	✓
Protocols and resident clients	
TCP/IP, DNS, DHCP, SNMP MIB II	✓
FTP, SSH	✓
802.1X Ethernet EAP/PEAP MSCHAPV2	✓
Citrix Receiver	13.1
Open VPN Client	2.1.3
Shell script session	Bash 4.2
Supports	
CUPS printing	Cups 1.4.6
LPD/LPR and RAW	Ipserver 1.1.6
Multimedia codecs	Factory option
Citrix H.264 Enhanced Supercoded	✓
Local application	
Adobe Flash Player	-
Supported environments	
Citrix XenApp 5 - 6.x - 7.x	✓
Citrix XenDesktop 5.x - 7.x	✓
Citrix VDI-in-a-box	✓
Centralized administration	
Central remote administration via ThinMan	✓
ThinMan Enterprise/Platinum profile manager support	✓
Remote Firmware update /VNC shadowing/ Wake on Lan	✓
Security password and screen saver password	✓
User interface	
Zero client VDI user interface mode (no local desktop)	✓
User interface with local desktop and applications bar	✓
Support multiple concurrent host connections	✓
Available factory options	
Add-on Praim MediaStream Codecs	Factory option
Power Over Ethernet (CLASS 4)	✓
Warranty	
Hardware warranty - On Center warranty coverage	4

Ver. 1.12 January 2016

Note: ✓ Installed / Supported - Not installed / Not supported ◇ Installable from the user based on available free disk space